


# BR8100IL

- Large Travel Bridge Mill
- Table : 80' x 100''
- Travels : 100'' x 80'' x 28''
- Control : 8200-B



Shown with options



**MILLTRONICS USA**  
LET'S INVENT

## SPECIFICATIONS:

<b>CAPACITY:</b>	
Travels	100 x 80 x 28" (2540 x 2030 x 710 mm)
Table Size	80 x 100" (2030 x 2540 mm)
Allowable Table Load	5000 lbs (2270 kg)

<b>SPINDLE:</b>	
Spindle Gage Line to Table Distance	4-32" (100-810 mm)
Spindle Taper	ISO No. 40 BIG PLUS®
Standard Spindle Speed	10,000 RPM
Optional Spindle Speed	15,000 RPM
Standard AC Spindle Motor	24/15 HP (18/11 kW) Inline 2 Speed
Optional AC Spindle Motor	35/25 HP (26/18 kW) Inline 2 Speed
Standard Spindle Torque	85 ft-lbs (115 N.m)
Optional Spindle Torque	122 ft-lbs (165 N.m)

<b>OPTIONAL AUTOMATIC TOOL CHANGER:</b>	
Number of Tools	24 Carousel
Tool Shank	CT40
Max. Tool Diameter	3.5" (89 mm)
Max. Tool Length	11" (280 mm)
Max. Tool Weight	15 lbs (7 kg)

<b>MOTION:</b>	
X/Y/Z Axis Rapid Traverse Rate	1000 IPM (25.4 m/min)
Max. Cutting Feed Rate	500 IPM (12.5 m/min)
X Axis Ballscrew Diameter	2.48" (63 mm)
Y Axis Ballscrew Diameter	1.57" (40 mm)
Z Axis Ballscrew Diameter	1.25" (32 mm)
Least Command Increment	0.0001" (0.001 mm)
Positioning Accuracy	+/- 0.001" (+/- 0.025 mm)
Positioning Accuracy (full travel)	+/- 0.005" (+/- 0.127 mm)
Repeatability	0.0003" (0.005 mm)
Axis Thrust Force	5000 lbs (2270 kg)

<b>GENERAL:</b>	
Machine Height	152" (3850 mm)
Floor Space Required (W x D)	280 x 164" (7125 x 4160 mm)
Machine Weight	19,500 lbs (8770 kg)
Power Required	48 KVA / 125 Amps
Voltage Required	208-240 Volts/3 Phase

## MACHINE FEATURES:

### MACHINE STANDARDS:

- Heavy duty 45 mm linear roller way construction X, Y, Z axis
- Precision ground double anchored ball screws
- Four bearing 10,000 RPM BIG-PLUS® dual contact inline spindle cartridge assembly
- Spindle tabber blow-out and tool release push button
- Front panel mounted electronic handwheel and handweel controlled program execution
- High torque closed loop vector spindle drive system with full regen
- Spindle load meter
- End of cycle light
- LCD hour meter
- High torque AC digital servo drives
- Single spare "M" function with CNC "wait" channel
- Edit key lock-out switch
- UL certified

### MACHINE OPTIONS:

- Coolant thru spindle (500 or 1000 psi)
- Coolant ready kit
- Chip management system (includes chip augers, chip channe troughs, lift-up chip conveyor, coolant system and modular enclosure)
- Programmable air blast nozzle
- Programmable spray mist
- Air thru spindle
- Rigid tap
- Spindle oil chiller
- Thermal head mapping
- 15,000 RPM spindle
- 35 hp spindle motor upgrade
- 24 station ATC
- Tool release foot switch
- 6" column riser
- Renishaw tool and part probing
- Spare M functions
- Remote handwheel
- Work light
- Keyboard
- Air gun
- Rotary tables
- Extended warranty
- Factory training



## 8200-B CNC

### The new standard of control

With its conversational programming, onscreen help, intuitive menus, color graphics and prompted tool settings, the 8200-B CNC helps new operators train faster and become more productive sooner. Shops can choose either conversational, G-code programming, or download tool paths created with a CAM system - whatever is the most efficient way to produce the required part.

### CONTROL STANDARDS:

- PC-based 8200-B CNC includes 1 GB parts storage memory
- Enhanced CPU with Block processing speed of 2000 bps with enhanced jerk control and look ahead
- Conversational plus G & M code programming including coordinate rotating, scaling, mirror image, thread mill engraving, helical interpolation, auto routines, and user definable macros with trig assist and irregular pocket clearing
- 12" LCD active matrix color display
- Auto DXF file import
- 3D part and wire frame tool path graphics plus solid modeling graphics
- Management software that allows editing of very large programfiles at the machine
- Spindle loader meter
- User definable macros with trig assist
- USB connectivity
- MTConnect compliant
- Networking

*Distributed By:*